

HOT SHOT SERIES



4012-10C



4012-15G

PORTABLE GASOLINE ENGINE 12V MODELS

3012-20G	2.5 GPM @ 4000 PSI	EX270	Subaru	GP Pump
3012-30G	3.0 GPM @ 3000 PSI	EX270	Subaru	GP Pump
3012-50G	3.0 GPM @ 2500 PSI	EX170	Subaru	GP Pump
4012-10A	4.0 GPM @ 4000 PSI	GX390	Honda	AR Pump
4012-10C	4.0 GPM @ 4000 PSI	GX390	Honda	CAT Pump
4012-10G	4.0 GPM @ 4000 PSI	GX390	Honda	GP Pump
4012-40G	4.0 GPM @ 2500 PSI	EX270	Subaru	GP Pump

PORTABLE DIESEL ENGINE 12V MODELS

4012-15C	4.0 GPM @ 3200 PSI	KD420ES	Kohler	CAT Pump
4012-15G	4.0 GPM @ 3200 PSI	KD420ES	Kohler	GP Pump

STANDARD FEATURES

- Rugged powder coated steel roll cage frame w/ lifting hook & pneumatic tires
- Super efficient schedule 80 coil w/ one-piece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank w/ fuel filter
- Commercial/Industrial grade engines
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Thermo-sensor (prevents over heating in bypass mode)

NOTE: Gasoline Honda and Diesel powered models include electric start, and battery w/ marine battery box. Subaru models are manual recoil start. All units are completely factory assembled, tested in the USA, and delivered ready to operate.

STANDARD ACCESSORIES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Maxi-Flo 20% chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle

AVAILABLE OPTIONS

ATK005 Adjustable Thermostat.
BRK100 Brake Kit.
HRK415 Hose Reel Kit, 150' x 3/8" max. w/no add'l hose.

AR, CAT, and GP gear & belt drive pumps available